

Manual for

SideTwix

Rhodes power supply

CAREFULLY READ THIS MANUAL BEFORE USING THE DEVICE! THE MANUAL IS PART OF THE DEVICE. IT CONTAINS IMPORTANT INFORMATIONS FOR OPERATION AND USAGE.

- Do never expose the device to rain or humidity. This will cause damage to the device.
- Repairs need to be done by qualified technicians only.
- Do not manipulate any jacks
- Do always shut off the device completely before cleaning. Wait till it is completely dry before connecting it to the power supply.



This device conforms EMC 89/336/EEC and LV 73/23/EEC

Assembled in Germany by

Tines & Reeds

ELECTRIC PIANO COMPANY

Christian Radtke
Bahnhofstr. 41
Werkstatt im Hinterhof
27383 Scheeßel
Tel.: 04263 912 17 87
Mobil: 0172 5496901
E-Mail: info@tinesandreeds.com
Web: <https://www.tinesandreeds.com>

CONCEPT & USAGE

SideTwix is a power supply for all 5pin Rhodes Suitcase preamps. Furthermore it's a great addition to our **MARK II Preamp**.

SideTwix comes with a headphone amplifier and can easily be mounted to the Rhodes piano with the enclosed bracket.

ATTENTION: Do make all connections *before* powering up the unit to prevent damage on the preamp.

FUNCTIONS

+15VDC:

Jack for the DC power adapter. **SideTwix** should be used with the enclosed power adapter. Anyway it can be used with other power adapters as well as long as they are supplying 9-18V. Plug: 5.5x2.1mm, inner plus.

CH.1 & 2:

Unbalanced audio outputs.

TO PIANO:

5pin XLR-jack for connecting **SideTwix** with the preamp. The cable is not part of the product and can be ordered separately.

PHONES:

Jack for the headphone. Use the volume potentiometer on the preamp to adjust the headphone volume.

TECHNICAL SPECIFICATIONS:

Power supply: External DC power adapter 9-18V @ 300mA, 5.5x2.1mm, inner plus

Dimensions: 123 x 55 x 44mm

Weight: 320g

Delivery contents: **SideTwix**, power supply, bracket, 2x M3x3 screws

Optional: 5pin XLR cable